## REVELATION

Pathway, Reveal, Wander

Milliken.

Modular Tile

**Construction** Tufted, Textured Loop

**Tile Size** 50 cm x 1 m (19.7" x 39.4")

Yarn Type Milliken-Certified WearOn<sup>®</sup> Nylon

Stain Resist / Soil Release StainSmart<sup>®</sup>

**Dye Method** PrintWorks<sup>™</sup> Precision Dyeing

**Tufted Face Weight** 28 oz/yd<sup>2</sup> (949.4 g/m<sup>2</sup>)

**Gauge** 1/12

**Stitches Per Inch** 9.6

**Tufts** 115/in<sup>2</sup> (1,781/100 cm<sup>2</sup>)

Finished Pile Height 0.12" (3.05 mm)

Average Density (Finished) 8,024 Standard Backing PVC-Free WellBAC® Comfort Plus Cushion Available with TractionBack®

**Recycled Content by Total Weight** Standard Backing: 34.9% Pre-Consumer, 0.0% Post-Consumer NSF 140 Platinum Backing Option: 26.6% Pre-Consumer, 10.0% Post-Consumer

**Embodied Carbon** 21.15 (kg CO<sub>2</sub>e)/m<sup>2</sup>

Nominal Total Thickness 0.41" (10.4 mm)

**Nominal Total Weight** 114.0 oz/yd<sup>2</sup> (3,865 g/m<sup>2</sup>)

Flammability (Radiant Panel ASTM-E-648) ≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or ASTM-E-662)  $\leq 450$ 

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859 Self-Extinguishing **Lightfastness (AATCC 16E)**  $\geq$  4.0 at 80 Hours

**Crocking (AATCC 165)**  $\geq$  4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H.,70° F. ≤ 3.5 KV, Permanent Conductive Fiber

**Texture Appearance Retention Rating** (**TARR**) Severe Traffic End-Use Applications

**Recommended Maintenance** MilliCare<sup>®</sup> Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label Plus™ GLP0793, Carpet Category 5Y

**Recommended Installation Method(s)** All Plank Methods

## WARRANTIES

Lifetime Face Fiber Wear Lifetime Antistatic Lifetime Floor Compatibility Lifetime Color Pattern Permanency Lifetime Floor Release

## Lifetime Cushion Resiliency Lifetime Moisture Resistance Lifetime Delamination of Back

Lifetime Delamination of Backing Lifetime Staining/Soiling (StainSmart®) Lifetime Dimensional Stability

CERTIFIC CREWING CR

Lifetime Tuft Bind Lifetime Edge Ravel Flammability

> This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Concierge 800.824.2246 | millikenfloors.com © 2022 Milliken & Company | Made in the USA