

Core



Product Specification

Construction Tufted High Low Loop
 Pile Material 100% Universal Nylon
 Dye Method 100% Solution Dyed
 Backing Unit Back® (PVC & Bitumen Free)

	Imperial	Metric
Pile Height	0.17 in	4.5mm±0.5mm
Tile Size	19.69 in X 19.69	50cm X 50cm
Stitch	12 in	49 / 10cm
Gauge	1/12 in	47.2 / 10cm
Pile Weight	18 oz/yd ²	610 g/m ²
Total Height	0.24 in	6±0.5mm

Functional properties

Wear classification 33-LC1
 Hexapod tumbler ISO 10361 12000 circle Grade≥3.5
 Use Density Heavy

Physical properties

Impact sound insulation ISO 10140 ca. 23dB
 Sound absorption ISO 354 $\alpha_w=0.25$
 Thermal resistance ISO 8302 ca. 0.07
 Burning classification DIN EN 13501-1 Cfl-s1
 Antistatic behavior ISO 6356 ≤2.0 kV
 Light fastness ISO 105 B02 ≥6
 Water fastness ISO 105 E01 ≥4
 Resistance to abrasion dry-wet ISO 105 X12 ≥3-4
 Tuft bind ISO 4919 ≥30N

Environmental Properties

GUT TVOC≤100µg/m³
 Declare Label
 EPD

Warrant

15 Years Limited Wear Warranty
 Lifetime Anti-Static Limited Warranty
 Lifetime Anti-Fade Limited Warranty


Certifications




Declare.



Installation



Monolithic



Brick