

Metro Park Stone

RigidForm™ SPC

SPECIFICATION

Construction	High Performance Rigid CoreTile
Finish	ProGuard™ Reinforced Polyurethane Coating
Wear Layer Thickness	0.55 mm
Overall Thickness	6.2 mm
Edge Profile	Micro Bevel
Tile Sizes	464mm x 935mm
Pieces Per Box	5
Weight Per Box	20.1 kg
Quantity Per Box	2.17 m ²

PERFORMANCE

Critical Radiant Flux (ASTM E648)	Pass - Class I
Smoke Density (ASTM E662)	Pass - ≤ 450
Heat Stability by Color Change (ASTM F1514)	Pass
Light Stability (ASTM F1515)	Pass
Static Coefficient of Friction (ASTM D2047)	Pass
Determination of dimensional stability and curling after exposure to heat (ISO 23999)	Pass
Resistance to Chemicals (ASTM F925)	Pass
ASTM E492 IIC Rating	70
ASTM E90 STC Rating	61
Static Load Limit (ASTM F970)	Pass

WARRANTIES

15-Year Limited Commercial Wear

Installation



SecureLock™ locking mechanism

3RD PARTY CERTIFICATES




Milliken LVT is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics. Milliken LVT is 100% ortho-phthalate-free. Milliken LVT is manufactured at facilities that are ISO 9001 and ISO 14001 compliant. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Images in this brochure are approximate for color and pattern scale. Please use actual product samples to make your final selections.